



Pléiades Glacier Observatory : DEM

Date : 2018-10-30
Site : Thana_ASC

DEM information

Coordinate system	UTM 46 north - EPSG 32646
Correlation algorithm	Semi Global Matching (SGM)
DEM resolution	2 m and 20 m
Reference for height	Ellipsoidal Height (WGS84)
Shift vector to Copernicus GLO-30 (m)	dx=+3.09; dy=-8.48; dz=-1.15
Base-to-Height ratio (B/H)	0.30

Source images

PHR	DS_PHR1A_201810300452043_FR1_PX_E090N28_0801_00660
PHR	DS_PHR1A_201810300452320_FR1_PX_E090N28_0801_00662

Copyright

Pléiades © CNES Year_of_acquisition, Distribution Airbus D&S

Archive structure

```

├─ 2018-10-30_0452413_Thana_ASC
│   ├── BM
│   ├── 2018-10-30_0452413_Thana_ASC_footprint.shp
│   ├── 2018-10-30_0452413_Thana_ASC_footprint.dbf
│   ├── 2018-10-30_0452413_Thana_ASC_footprint.prj
│   ├── 2018-10-30_0452413_Thana_ASC_footprint.shx
│   └─ SGM
│       ├── 2018-10-30_0452413_Thana_ASC_DEM_SGM_2m.tif
│       ├── 2018-10-30_0452413_Thana_ASC_DEM_SGM_20m.tif
│       ├── README_SGM_DEM.pdf
│       ├── PREVIEW_2018-10-30_0452413_Thana_ASC_DEM_SGM_20m.png
│       └─ COREGISTRATION_RESULT_2018-10-30_0452413_Thana_ASC_DEM_SGM_20m.png

```

Description

DEMs and orthoimages were generated from raw Pléiades images using the Ames Stereo Pipeline [Beyer et al., 2018]. The set of processing parameters used for DEM generation are from [Marti et al., TC, 2016] for block matching -BM- and from [Deschamps-Berger et al., 2020] for semi global matching -SGM.

All DEMs and orthoimages are coregistered on the Copernicus GLO-30 DEM using the demcoreg tool [Shean et al., 2021].

Acknowledgement statement: The Pléiades images/DEMs used in this study was provided by the Pléiades Glacier Observatory initiative of the French Space Agency (CNES) and Laboratoire d'Etudes en Géophysique et Océanographie Spatiales (LEGOS).

When an image is shown in a presentation, website or an article, the copyright should be (Pléiades © CNES Year_of_acquisition, Distribution Airbus D&S).

We remind to cope with the licence rules regarding (no) data sharing and no commercial use.

References

- Beyer et al.: The Ames Stereo Pipeline: NASA's Open Source Software for Deriving and Processing Terrain Data, Earth and Space Science, 5(9), 537–548, doi:10.1029/2018EA000409, 2018.
- Shean et al.: dshean/demcoreg, Zenodo, v1.1.0, <https://doi.org/10.5281/zenodo.5733347>, 2021.
- Deschamps-Berger et al.: Snow depth mapping from stereo satellite imagery in mountainous terrain: evaluation using airborne laser-scanning data, The Cryosphere, 14(9), 2925–2940, <https://doi.org/10.5194/tc-14-2925-2020>, 2020.
- Marti et al.: Mapping snow depth in open alpine terrain from stereo satellite imagery, The Cryosphere, 10(4), 1361–1380, doi:10.5194/tc-10-1361-2016, 2016.